



FARROW FLOW® POWDER COATING INSERT

FF-1787-P

THE FIRST, THE FASTEST, THE FUTURE

Thank you for your purchase!

The Farrow Flow® insert for Powder Coating guns is the only patented insert of its kind designed to spin the air in a vortex pattern inside of your airline before the tip to provide you with a wider paint pattern at the tip saving you time, powder while providing improved first pass transfer efficiency.

Included in this Package:

- (a) ONE (1) Farrow Flow Insert for POWDER COATING
- (b) TWO (2) Straight Connectors:
 - 10MM Push to Connect X 8MM Push to Connect



Installation Instructions

1	Turn off air supply to powder system.
2	Disconnect air line at the regulator.
3.	Make one clean straight cut in the air hose leading to the gun.
4.	Insert the Farrow Flow assembly by gently pushing the hose into the straight connectors.
5.	Reconnect air supply to powder system.
6.	Before you begin painting, check to be sure air pressure is below 75psi in your air line to prevent damage to the insert.
7.	Decrease powder dosage when necessary.
8.	Paint as usual.
*	Tip 💡 : Remember to adjust powder dosage once inserted and adjust distance accordingly to get the full advantage of the FARROW FLOW insert.



FARROW FLOW, INC.

Downingtown, PA 19335

info@farrowflow.com

www.farrowflow.com

484-359-1900

Specifications

Length	10" / 254mm
Width	.75" / 19.05mm
Material	Thermoplastic Polyurethane (BPA and Styrene free)
Part#	FF-1787-P
Weight	16oz / 1lb
Straight Connector: 10MM X 8MM Push to Connect	Nylon



Safety Warning

- *Inserts are delivered factory assembled and ready for connection with a 8mm connector.*
- *Prior to installation, check air pressure is below 75psi in your air line to prevent damage to the insert assembly.*
- *Do not exceed maximum 75 psi while Farrow Flow is inserted inline.*
- *Shut down air supply prior to any adjustment, connection installation or removal of the Farrow Flow insert assembly.*
- **TO CLEAN THE FARROW FLOW INSERT, USE MILD SOAP AND WATER ONLY!**
- *DO NOT use cleansing agents such as acetone, benzene, carbon tetrachloride, gasoline, toluene etc. which are damaging to the plastic.*
- *Do not use wrenches or pipe grips on the Farrow Flow as this could cause damage to the insert assembly.*

We value your trust in our product and welcome your feedback!